



unwind(8) - florian@OpenBSD.org

- OpenBSD developer since 2012
 - author of slowcgi(8), slaacd(8) (cf. BSDCan 2018), rad(8), unwind(8), sysupgrade(8), ...
 - poked at things in the network stack
 - 1744 files changed, 229095 insertions(+), 337080 deletions(-)
- Senior Systems Engineer @ RIPE NCC
 - BGP, DNS, ...
 - k.root-servers.net, ...




A Day in the Life of a Root Name Server




■ The Problem and A Solution



A recursive name server for every laptop



Opportunistic DNSSEC validation



Captive-portal handling



Adapt to local conditions...



... no matter how harsh.




Previous approaches

- dhclient(8)
 - Just owns /etc/resolv.conf
 - Will get you past captive-portals
 - At the mercy of recursive name server operator
 - No DNSSEC
 - No privacy
 - Same address space

- static configuration
 - Tell dhclient to leave /etc/resolv.conf alone
 - Will likely not get you past captive-portals
 - Will not work in places where DNS is filtered
 - No DNSSEC
 - No privacy
 - Same address space

- run unbound(8) on localhost
 - Tell dhclient to leave /etc/resolv.conf alone
 - DNSSEC validation
 - Privacy: (DoT) if configured
 - Will likely not get you past captive-portals
 - Will not work in places where DNS is filtered
 - Different address space

- Others
 - systemd-resolved
 - openresolv / resolvconf
 - stubby
 - dnsmasq
 - dnscrypt-proxy



Welcome unwind(8).

- Run unwind(8) on localhost
 - Tell dhclient to leave /etc/resolv.conf alone
 - DNSSEC validation
 - Privacy: (DoT) if configured
 - Will get you past captive-portals
 - Will work in places where DNS is filtered
 - Different address space

- Architecture
 - Three processes privileg seperated daemon
 - Design copied from bgpd, ospfd, rad, slaacd...
 - IPC over pipes
 - Config file & reload
 - Logging to syslog & stderr
 - Control tool
 - pledge(2) for restricted service operating mode
 - see www.openbsd.org/events.html

- Parent process
 - Starts everything up
 - Opens localhost 53/udp & passes to frontend
 - Asks dhclient & slaacd to send forwarders
 - pledge("stdio rpath sendfd");
 - Config parsing & reload

- Frontend process
 - pledge("stdio unix recvfd");
 - Receives queries on 53/udp
 - Parses query
 - Passes query to resolver
 - Sends back response
 - Handles control socket
 - Listens for interfaces going up / down
 - Listens for learned forwarders

- Resolver process
 - All the heavy DNS lifting
 - Keeps track of resolving strategies
 - Receives query from frontend
 - Hands query to "best" strategy
 - Sends answer back to frontend
 - pledge("stdio inet rpath");
 - unveil("/etc/ssl/cert.pem", "r");



Relax...

- Resolver: libunbound
 - Does most of the resolving for us
 - Local copy
 - Not a fork; kept in sync with upstream
 - We need to poke at some internals

- Resolver: Strategies (1/2)
 - Without config file:
 - recursor
 - dhcp / slaac forwarder
 - dhcp / slaac opportunistic DoT forwarder
 - dhcp / slaac stub forwarder
 - With config file:
 - DoT forwarders with authentication name
 - static forwarders
 - Default preference: DoT forwarder recursor dhcp stub

- Resolver: Strategies (2/2)
 - individual libunbound contexts
 - (except stub: asr(3) libc asynchronous resolver)
 - shared cache
 - single threaded, plugged together with libevent

- Resolver: Health & quality checks (1/2)
 - . IN SOA
 - Known to exist
 - DNSSEC signed
 - Strategy state
 - VALIDATING
 - RESOLVING
 - UNKNOWN
 - DEAD

- Resolver: Health & quality checks (2/2)
 - Track query round trip time
 - Keep a (decaying) histogram per strategy
 - Calculate median RTT

recursor validating, 50ms 4. DoT validating, 150ms
forwarder validating, 30ms 5. stub resolving, N/A
dhcp validating, 70ms

	histograms: lifetime[ms], decaying[ms]											
	<10	<20	<40	<60	<80	<100	<200	<400	<600	<800	<1000	>
rec	15664	413	1784	1363	809	552	987	601	206	55	44	425
	11	0	2	2	0	0	1	0	0	0	0	0
forw	312	63	68	36	37	48	138	124	88	24	12	446
	0	0	0	0	0	0	0	0	0	0	0	0
dhcp	33	7	7	1	3	0	2	4	1	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0
DoT	33	0	0	4	26	25	82	43	28	25	11	696
	0	0	0	0	0	0	0	0	0	0	0	0
stub	0	0	1	0	0	0	0	0	0	0	0	0
	0	0	0	0	0	0	0	0	0	0	0	0

- Resolving
 - Sort strategies
 - VALIDATING > RESOLVING
 - Median RTT
 - Prefered strategy skewed by 200ms
 - Pick best; call ub_resolve_event()
 - Wait median RTT ms; no answer:
 - Try next best strategy
 - Do not cancel running queries



Captive Portals & DNS breakage

- Captive Portals (1/5)
 - Unwind used to have an http checker...
 - ... but we couldn't agree on a built-in URL

- Captive Portals (2/5)
 - Everything blocked except dhcp forwarders
 - → use those

- Captive Portals (3/5)
 - Everything blocked except dhcp forwarders or DNS gets intercepted
 - SERVFAIL or NXDOMAIN with edns0
 - → use stub

- Captive Portals (4/5)
 - DNS open
 - 1st (or 2nd!) http redirect results in NXDOMAIN
 - Heuristic: Do not trust NXDOMAIN
 - → use stub

- Captive Portals (5/5)
 - DNS open
 - Portal domain DNSSEC signed
 - No signature for portal host
 - Heuristic: Do not trust validation errrors
 - → use stub



Future work

- Future work
 - Wifi vs 4g
 - DNSSEC validation too opportunistic
 - Dedicated TCP strategy
 - Track captive portal URL domains
 - don't use shared cache behind captive portals
 - DNS64



Questions?



Come on! Don't be shy!